

FMJ Series

6FMJ-65 12V65Ah

FMJ series gel batteries utilize advanced battery technology. FMJ has good cyclic performance and high reliability. It is the economical choice for solar photovoltaic street lights, garden and lawn lamps, traffic lights, warning lights and other energy storage systems.

Benefits

- Long life according to EUROBAT Classification
- High discharge performance
- High gas recombination efficiency
- Maximum charge efficiency
- GEL state electrolyte prevents leakage and layering
- Low resistance PVC or PF micro-porous separator ensure low self-discharge rate
- Easy installation and handling


Applications

- Telecommunications
- Emergency power
- Energy storage systems
- UPS units
- Electrical Power plants and substation

Standards

- IEC 60896-21/22
- IEC 61427
- DIN 43539-T5
- EUROBAT guide

Drawing



Specifications


Battery Model	6FMJ-65			
Design Life (years, 25°C)	15			
Capacity (Ah, 25°C)	10HR (6.5A, 1.80V)	5HR (11.05A, 1.80V)	3HR (16.25A, 1.80V)	1HR(34.99A, 1.80V)
	65	55.25	48.75	34.99
Dimensions (mm)	Length	Width	Height	Total Height
	310	174	226.5	236.5
Approx. Weight (kg)	27.0			
Reference Internal Resistance (mΩ)	7.25±15% (full charged @ 25 °C ,testing device:HIOKI BT3562)			
Maximum Discharge Current (A/3 Sec.)	828			
Self-Discharge (25°C)	≤ 3 % per month			
Charge Voltage (V/cell, 25°C)	Cycle use		Float use	
	2.33 (-3.5mV/°C/cell), max charge current: 13A		2.23 (-3.5mV/°C/cell)	
Short Circuit Current (A)	1400			

Discharge Data


Constant Current Discharge Data (25°C, A)																		
End Voltage (V/cell)	min			h														
	15	30	45	1	1.5	2	3	4	5	6	8	10	20	24	48	100	120	240
1.60	101.4	64.97	45.34	38.32	29.19	22.79	17.78	14.24	12.10	11.02	8.541	7.118	3.666	3.094	1.541	0.741	0.709	0.371
1.65	98.35	63.67	44.43	37.56	28.61	22.33	17.43	13.95	11.86	10.81	8.372	6.975	3.588	3.036	1.508	0.735	0.702	0.364
1.70	95.36	62.40	43.55	36.81	28.03	21.91	17.06	13.67	11.62	10.60	8.203	6.832	3.517	2.977	1.489	0.728	0.696	0.358
1.75	92.56	61.15	42.61	36.08	27.47	21.45	16.72	13.40	11.38	10.38	8.041	6.695	3.452	2.919	1.463	0.722	0.689	0.351
1.80	87.95	59.31	41.40	34.99	26.65	20.81	16.25	13.00	11.05	10.08	7.800	6.500	3.380	2.860	1.443	0.715	0.683	0.345

Constant Power Discharge Data (25°C, W/cell)																		
End Voltage (V/cell)	min			h														
	15	30	45	1	1.5	2	3	4	5	6	8	10	20	24	48	100	120	240
1.60	176	114	79.35	67.45	51.37	40.11	31.83	25.91	22.15	20.06	15.72	13.24	7.039	6.002	3.019	1.475	1.417	0.748
1.65	173	113	78.65	66.85	51.21	39.98	31.73	25.67	21.93	20.00	15.57	13.18	6.961	5.950	2.986	1.469	1.411	0.739
1.70	170	112	77.95	66.26	50.74	39.87	31.40	25.29	21.73	19.92	15.50	13.12	6.892	5.924	2.962	1.463	1.405	0.729
1.75	168	111	77.56	65.66	50.54	39.68	31.10	25.06	21.50	19.83	15.44	13.06	6.799	5.837	2.925	1.457	1.399	0.720
1.80	164	110	76.59	65.08	50.10	39.53	30.88	24.83	21.33	19.65	15.29	12.87	6.760	5.749	2.900	1.451	1.392	0.710


Performance Curve




Discharge voltage vs. discharge time



Charge vs. discharge depth



Capacity vs. temperature



Design life vs. temperature

Sacred Sun Power Sources Co., Ltd.

Add: No.1 Shengyang Road, Qufu 273100 PRC
 Tel: +86-537-4422313 Fax: +86-537-4411980
 Email: sales@sacredsunsun.cn

Sacred Sun Hong Kong Co., Limited

Add: RM 19C Lockhart CTR 301-307 Lockhart RD Wan Chai, Hong Kong
 Email: admin.hk@sacredsunsun.hk

Sacred Sun Asia Pacific Pte Ltd.

Add: 1 Ubi View, #04-12, Focus One, Singapore 408555
 Email: admin.sg@sacredsunsun.sg

Sacred Sun Europe SARL

Add: ZAE Fontaine, 33210 Fargues, France
 Email: admin.eu@sacredsunsun.eu

Sacred Sun MEA FZE

Add: No. 311 office, Building LOB 14, JAFZA, Dubai, UAE
 Email: admin.ae@sacredsunsun.ae

