

SP Series

SSP12-5 12V5Ah

SP series VRLA battery uses AGM technology and high-purity raw materials. Its good floating back up and large current discharge performance makes it optimal and economical choice for UPS/EPS.

Benefits

- Long life according to EUROBAT Classification
- Maximum charge efficiency
- High gas recombination efficiency
- Low self-discharge rate
- Easy installation and handling
- Vertical installation


Applications

- UPS units
- Emergency power
- Fire and safety alarm system
- EPS units

Standards

- IEC 61056-1/2
- JIS C8702-1/2
- EUROBAT guide

Drawing



Specifications

Battery Model	SSP12-5			
Design Life (years, 25°C)	5			
Capacity (Ah, 25°C)	20HR (0.25A, 1.75V)	10HR (0.485A, 1.75V)	5HR (0.855A, 1.75V)	1HR(3.43A, 1.70V)
	5	4.85	4.27	3.43
Dimensions (mm)	Length	Width	Height	Total Height
	90	70	101	107
Approx. Weight (kg)	1.62			
Reference Internal Resistance (mΩ)	22±15%(full charged @ 25°C,testing device:HIOKIBT3562)			
Maximum Discharge Current (A/3 Sec.)	75			
Self-Discharge (25°C)	≤ 2% per month			
Charge Voltage (V/cell, 25°C)	Cycle use		Float use	
	2.45 (-4mV/°C/cell), max charge current: 1.5A		2.27 (-3.5mV/°C/cell)	
Short Circuit Current (A)	150(For reference only)			

Discharge Data





Constant Current Discharge Data (25°C, A)

End Voltage (V/cell)	min						h					
	10	15	20	30	45	60	1.5	2	3	5	10	20
1.60	13.2	10.2	7.20	5.87	3.98	3.47	2.58	1.81	1.28	0.870	0.500	0.280
1.65	12.7	9.83	7.08	5.78	3.96	3.45	2.57	1.80	1.28	0.865	0.495	0.270
1.70	12.3	9.60	7.02	5.73	3.95	3.43	2.55	1.78	1.27	0.860	0.490	0.260
1.75	11.5	9.10	6.82	5.60	3.90	3.38	2.53	1.77	1.27	0.855	0.485	0.250
1.80	10.7	8.60	6.62	5.47	3.83	3.28	2.48	1.74	1.26	0.850	0.474	0.245

Constant Power Discharge Data (25°C, W/cell)

End Voltage (V/cell)	min						h					
	10	15	20	30	45	60	1.5	2	3	5	10	20
1.60	23.4	19.0	13.9	11.7	7.68	6.94	4.90	3.60	2.56	2.05	0.985	0.550
1.65	23.0	18.7	13.8	11.5	7.63	6.92	4.88	3.58	2.55	2.04	0.975	0.530
1.70	22.7	18.3	13.4	11.4	7.57	6.90	4.86	3.56	2.54	2.03	0.965	0.520
1.75	21.7	17.4	13.0	11.2	7.50	6.78	4.84	3.53	2.52	2.02	0.954	0.500
1.80	20.3	16.4	12.6	10.8	7.42	6.67	4.80	3.48	2.50	2.00	0.938	0.485

Performance Curve


Sacred Sun Power Sources Co., Ltd.

Add: No.1 Shengyang Road, Qufu 273100 PRC
 Tel: +86-537-4422313 Fax: +86-537-4411980
 Email: sales@sacredsunsun.com

Sacred Sun Hong Kong Co., Limited

Add: RM 19C Lockhart CTR 301-307 Lockhart RD Wan Chai, Hong Kong
 Email: admin.hk@sacredsunsun.com

Sacred Sun Asia Pacific Pte Ltd.

Add: 1 Ubi View, #04-12, Focus One, Singapore 408555
 Email: admin.sg@sacredsunsun.com

Sacred Sun Europe SARL

Add: ZAE Fontaine, 33210 Fargues, France
 Email: admin.eu@sacredsunsun.com

Sacred Sun MEA FZE

Add: No. 311 office, Building LOB 14, JAFZA, Dubai, UAE
 Email: admin.ae@sacredsunsun.com

