

FT Series

FTA12-180 12V180Ah

Sacred Sun front terminal batteries have been designed specifically for applications which demand the highest levels of security and reliability. The monoblocs have excellent high rate performance, compact design and standard footprint for 19" and 23" cabinets. Thick Pb-Ca-Sn alloy grids are designed to resist corrosion and prolong service life.

Benefits

- Long life according to EUROBAT Classification
- High discharge performance
- High gas recombination efficiency
- Maximum charge efficiency
- Low self-discharge rate
- Easy installation and handling
- Centralized venting system


Applications

- Telecommunications
- Power system
- UPS
- Emergency power
- Data center

Standards

- IEC 60896-21/22
- BS 6290-4
- EUROBAT guide

Drawing



Specifications


Battery Model	FTA12-180			
Design Life (years, 25°C)	12			
Capacity (Ah, 25°C)	10HR (18.0A, 1.80V)	5HR (30.79A, 1.80V)	3HR (45.05A, 1.80V)	1HR(99.5A, 1.75V)
	180	153.95	135.15	99.50
Dimensions (mm)	Length	Width	Height	Total Height
	560	125	310	310
Approx. Weight (kg)	52.80			
Reference Internal Resistance (mΩ)	3.6 ±15% (fully charged @ 25°C, Testing device: HIOKIBT3562)			
Maximum Discharge Current (A/3 Sec.)	1550			
Self-Discharge (25°C)	≤ 1.5% per month			
Charge Voltage (V/cell, 25°C)	Cycle use		Float use	
	2.35 (-3.5mV/°C/cell), max charge current: 34A		2.25 (-3.5mV/°C/cell)	
Short Circuit Current (A)	3650			

Discharge Data


Constant Current Discharge Data (25°C, A)											
End Voltage (V/cell)	min		h								
	30	45	1	2	3	4	5	6	8	10	20
1.60	195.8	135.2	110.4	67.7	50.1	39.44	33.63	28.89	23.12	19.14	10.04
1.65	185.4	128.6	105.3	65	48.36	38.15	32.59	28.14	22.64	18.76	9.85
1.70	180.7	125.7	103.1	63.9	47.62	37.6	32.21	27.76	22.36	18.57	9.76
1.75	173.2	121.2	99.5	62	46.33	36.68	31.55	27.19	21.98	18.28	9.66
1.80	165.6	116.4	95.9	60.1	45.05	35.76	30.79	26.62	21.6	18	9.57

Constant Power Discharge Data (25°C, W/cell)											
End Voltage (V/cell)	min		h								
	30	45	1	2	3	4	5	6	8	10	20
1.60	343	239	196.2	122.1	91.1	72.02	61.75	53.22	42.71	35.51	18.68
1.65	328.8	229.7	188.9	118	88.4	70.02	60.01	51.97	41.98	34.91	18.38
1.70	322.4	225.8	186	116.5	87.35	69.24	59.5	51.43	41.64	34.71	18.29
1.75	311.7	219.3	180.6	113.5	85.26	67.76	58.43	50.53	41.02	34.26	18.17
1.80	300.8	212.4	175.4	110.7	83.43	66.36	57.26	49.63	40.41	33.79	18.04


Performance Curve




Discharge voltage vs. discharge time



Charge capacity vs. charge time



Discharge capacity vs. temperature



Design life vs. temperature

Sacred Sun Power Sources Co., Ltd.

Add: No.1 Shengyang Road, Qufu 273100 PRC
 Tel: +86-537-4422313 Fax: +86-537-4411980
 Email: sales@sacredsunsun.cn

Sacred Sun Hong Kong Co., Limited

Add: RM 19C Lockhart CTR 301-307 Lockhart RD Wan Chai, Hong Kong
 Email: admin.hk@sacredsunsun.hk

Sacred Sun Asia Pacific Pte Ltd.

Add: 1 Ubi View, #04-12, Focus One, Singapore 408555
 Email: admin.sg@sacredsunsun.sg

Sacred Sun Europe SARL

Add: ZAE Fontaine, 33210 Fargues, France
 Email: admin.eu@sacredsunsun.eu

Sacred Sun MEA FZE

Add: No. 311 office, Building LOB 14, JAFZA, Dubai, UAE
 Email: admin.ae@sacredsunsun.ae

